



NEW

pro clima

CONTEGA[®] SOLIDO EXO

Full-surface adhesive sealing tape for exterior use that is open to diffusion and can be plastered over

The CONTEGA SOLIDO EXO joint adhesive tape, which is full-surface adhesive and can be plastered over, ensures exterior windtight and diffusion-permeable sealing of windows and doors to adjacent building components made of wood and mineral materials such as concrete and sand-lime brick.

The modified waterproof SOLID adhesive ensures quick and permanent adhesion to the subsurface.

- ✓ Full-surface adhesive, the joint is immediately windproof and resistant to driving rain, and it can be subjected to loading
- ✓ Extremely strong adhesion on mineral subsurfaces too thanks to modified waterproof SOLID adhesive
- ✓ Can be plastered over
- ✓ Tape for joints on or under window frames
- ✓ Easy to apply



www.proclima.com

... and the insulation
is perfect



pro clima CONTEGA[®] SOLIDO EXO

Full-surface adhesive sealing tape for exterior use that is open to diffusion and can be plastered over



Technical data:

		Substance
Backing		PP backing fleece, PP copolymer special membrane
Adhesive		modified waterproof SOLID adhesive
Release film		one or two split silicone-coated PE sheet
Attribute	Regulation	Value
Colour		black
s_g -/g-value	EN 1931	0.7 m / 3.5 MNs/g
Exposure time		3 months
Can be plastered over		yes
IFT tested (DE-Rosenheim)	MO-01/1:2007-01	yes
Application temperature		above -10 °C
Temperature resistance		permanent -40 °C to +90 °C
Storage		cool and dry

Forms of delivery:

Itemnumber	EAN	Length	Width	PU	PU / Pal.	Weight (kg/PU)
15439	4026639154392	30 m	8 cm	8	48	7,7
15440	4026639154408	30 m	10 cm	8	36	9,6
15441	4026639154415	30 m	15 cm	4	48	7,2
15442	4026639154422	30 m	20 cm	4	36	9,6

Situation 1 Window has already been installed

Stick to the frame



1 Remove the narrow backing paper strip. Put the CONTEGA SOLIDO EXO in place using the full width of the adhesive strip and allowing for an excess of 2 cm beyond the corner of the frame. Stick the excess tape to the adjacent soffit side.

Stick to the soffit allowing for slack



2 Remove the backing paper strip and gradually stick the tape in place on the soffit. Leave slack for expansion so as to allow for relative motion between components. Stick the tape to the window sill.

Stick the corners and around the circumference of the window



3 Continue sticking the entire window (frame and soffit) in the same manner. Ensure that the corners are stuck over.

Situation 2 Before the window is installed

Stick to the side of the frame



1 Remove the narrow backing paper strip, position it on the side of the frame flush with the frame edge and then stick in place. The printed side of the tape facing up.

Corner finishing



2 To ensure that the tape can be simply and securely stuck to the window soffit later on, create corner folds as shown here and stick CONTEGA SOLIDO EXO around the circumference.

Stick to the soffit



3 Remove the backing paper strip and stick the tape in place around the circumference of the soffit.

Further information about application and construction is given in the pro clima planning documentation and application recommendations.

(Please also note the recommendations of the currently valid version of the pro clima application matrix.)

If you have any questions, please call the pro clima technical hotline Ireland and UK:

☎ +353 46 9432104

☎ +353 46 9432435

✉ info@ecologicalbuildingsystems.com

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Germany
☎ +49 (0) 62 02 - 27 82.0
☎ +49 (0) 62 02 - 27 82.21
✉ info@proclima.com

www.proclima.com pro clima[®]

